

taylordolman

pojlock
Lifts

1m Independence Steplift

the next generation in elegant access solutions



taylordolman tel: 0845 838 0600 email: info@taylordolman.com

1m Independence Steplift

the next generation in elegant access solutions

The **2-piece system** Independence Steplift from Pollock Lifts continues to provide strength and modern aesthetics with a host of new and improved features. Now a more extensive range offering a variety of platform sizes, entry configurations and bespoke options to suit your environment.

3 PLATFORM SIZES

740mm Standard*

(DDA compliant)

800mm*

(Part M Compliant platform for through entry)

1100mm*

(Part M Compliant platform for adjacent entry)

*Indicates clear access width

5 CONFIGURATIONS

Through Entry

Adjacent Entry/Exit

Bridging Steps

Choose from 1, 2 or 3 steps
(max. travel of 750mm)

Pit Mounted

(Requires 90mm pit for use when space is restricted)

Bespoke

KEY FEATURES AND BENEFITS

- › Pump unit is integrated within the gate offering reduced vandalism risk
- › No need for separate control unit or pump location
- › Easy access to pump for servicing
- › Easier and faster to install
- › Simpler to use
- › More compact
- › New stylish protective bellows - more rigid/durable
- › Improved IP 67 rated switching (waterproof) with easy service access
- › Easy to use emergency lowering system

Standard Features

- › Travel up to 1m
- › Maximum capacity of 250 kg
- › Suitable for internal or external use (Weatherproof)
- › Battery operated hydraulic power with mains back-up
- › Key operated call stations
- › Easy installation and low maintenance
- › Can be relocated
- › Full platform safety edge as standard
- › Auto reverse safety system on ramp
- › Locking system to secure ramp in UP position
- › Designed to BS 6440, TUV and CE approved

Optional Features

- › Interlocking gate
- › Automatic gate open and close
- › Choose from alternative RAL colours
- › Vandal guards on call stations
- › Customised control options
- › Bespoke designs and finishes

Through Entry:

Models	Internal Dimensions	External Dimensions
740mm Standard	740 x 1400	975 x 1995
800mm	800 x 1400	1065 x 1995
1100mm	1100 x 1400	1355 x 1995

All measurements are in millimetres (mm)



Adjacent Entry:

Models	Internal Dimensions	External Dimensions
740mm Standard	860 x 1400	1135 x 1835
800mm	950 x 1400	1225 x 1835
1100mm	1240 x 1400	1515 x 1835

All measurements are in millimetres (mm)



Bridging Steps:

Models	Internal Dimensions	External Dimensions
740mm Standard	740 x 1400	TBA
800mm	830 x 1400	TBA

All measurements are in millimetres (mm)



Pit Mounted:

Models	Internal Dimensions	External Dimensions	Pit
740mm Standard	740 x 1400	995 x 1580	80
800mm	800 x 1400	1085 x 1580	80
1100mm	1100 x 1400	1375 x 1580	80

All measurements are in millimetres (mm)



NOTE: Photographs are for guidance only.
Lift style and finishes are dependant on model and optional features selected.



Also from Pollock Lifts...



2m Independence Steplift Range

...reaching new heights with 2 metre lift access



Through-floor Lift Range

...elevating excellence with a modern and unobtrusive 2 floor access solution



Disabled Access Range

...offering freedom in any environment with multi-level access lifts

taylordolman

tel: 0845 838 0600

email: info@taylordolman.com

www.taylordolman.com